

CLAIMS

1. An organic electroluminescent device comprising
a pair of electrodes, and
5 at least two organic emitting layers held between
the pair of electrodes,

(1) two organic emitting layers being arranged
with an electron barrier layer interposed therebetween,

(2) the two organic emitting layers both
10 comprising an electron-transporting emitting material.

2. The organic electroluminescent device according to
claim 1, wherein the two organic emitting layers both have
an electron mobility of 10^{-6} cm²/V·sec or more.

15

3. The organic electroluminescent device according to
claim 1, wherein the electron barrier layer has an
affinity level of at least 0.2 eV less than the affinity
level of the organic emitting layer arranged on a cathode
20 side relative to the electron barrier layer

20

4. The organic electroluminescent device according to
claim 1, wherein a difference in ionization potential
between the electron barrier layer and the organic
25 emitting layer arranged on an anode side relative to the
electron barrier layer is 0.2 eV or less.

25

5. The organic electroluminescent device according to
claim 1, wherein a difference in ionization potential
30 between the electron barrier layer and the organic

30

emitting layer arranged on a cathode side relative to the electron barrier layer is 0.2 eV or less.

6. The organic electroluminescent device according to claim 1, wherein the organic emitting layer arranged on an anode side relative to the electron barrier layer emits blue light.

7. The organic electroluminescent device according to claim 6, wherein the organic emitting layer arranged on a cathode side relative to the electron barrier layer emits yellow to red light.

8. The organic electroluminescent device according to claim 1, wherein the organic emitting layer arranged on an anode side relative to the electron barrier layer emits yellow to red light.

9. The organic electroluminescent device according to claim 8, wherein the organic emitting layer arranged on a cathode side relative to the electron barrier layer emits blue light.

10. The organic electroluminescent device according to claim 6 or 9, wherein the maximum wavelength of the blue light is 450 nm to 500 nm.

11. The organic electroluminescent device according to claim 7 or 8, wherein the maximum wavelength of the yellow to red light is 540 nm to 700 nm.

12. The organic electroluminescent device according to claim 1 that emits white light.

5 13. A display comprising the organic electroluminescent device of claim 1.